

## **ClearOne Introduces New Two-Channel Wireless Microphone System DIALOG® 20 System Opens New Market Opportunities for ClearOne Partners**

SALT LAKE CITY, June 2, 2016 /PRNewswire/ -- ClearOne [NASDAQ: CLRO] is introducing the new compact two-channel DIALOG 20 — a system packed with innovative features that increases the breadth of its wireless microphone product line. DIALOG 20 targets uses in which only a few wireless mics are required, e.g., classrooms, presentation and training venues, huddle and other spaces.

"With its small form factor, the new DIALOG 20 incorporates flexible features and delivers multiple options that satisfy users' specific needs," ClearOne Sales Director, Wireless Microphone Solutions for North & Central America, John Nygren said. "DIALOG 20 combines ease of setup, ease of use, adaptability, and security all in one affordable package."

Using robust adaptive frequency-hopping spread spectrum technology within the 2.4 GHz unlicensed spectrum, DIALOG 20 has several advantages over fixed frequency transmission. First, DIALOG 20 is resistant to narrowband interference because it switches frequency using a pseudo-random sequence. Second, this sequencing makes the frequency-hopping signals very difficult to intercept. Third, the use of 128 bit AES encryption on each hopped frequency further secures the wireless audio transmission.

The unlicensed spectrum allows DIALOG 20 users to employ the same model with the same frequency plan worldwide, without being concerned about regulatory frequency restrictions or limitations by locale or country.

DIALOG 20 comes with four transmitter options: handheld, belt-pack, gooseneck podium, and tabletop version with programmable buttons.

Each of the microphone transmitters has additional options suitable for any application. The podium has six-, 12-, and 18-inch gooseneck options. The handheld offers cardioid, super-cardioid, and hyper-cardioid heads. The belt-pack has clip-on and headset versions, while the tabletop boundary transmitter offers omni and cardioid mics.

While the new DIALOG 20 works seamlessly with all commercially available mixers, it boasts additional features when natively interfacing with ClearOne's new CONVERGE® Pro 2 or new Beamforming Microphone Array 2. These features include powering DIALOG 20 receivers from a CONVERGE Pro 2 mixer or Beamforming Microphone Array 2 as well as daisy-chaining up to three DIALOG 20 receivers.

When not connected to CONVERGE Pro 2, the wireless receiver can be powered through either the micro USB port or PoE (Power over Ethernet) injector.

The receivers may be mounted on a rack shelf, a wall or ceiling. Equipped with an integrated antenna, DIALOG 20 offers an option to extend the antennae up to 20 feet away. The receivers can be configured and monitored using a Windows® software application. A Mac OS version is coming soon.

DIALOG 20 will be on display at InfoComm 2016.

For details on ClearOne's wireless microphone solutions, contact ClearOne Sales at

1-801-975-7200 or visit: [http://www.clearone.com/wireless\\_microphone\\_systems](http://www.clearone.com/wireless_microphone_systems)

*Let ClearOne Open Your World to New Solutions at InfoComm16, June 8-10, Booth N1837.*

### **About ClearOne**


ClearOne is a global company that designs, develops, and sells conferencing, collaboration, and network streaming & signage solutions for voice and visual communications. The performance and simplicity of its advanced comprehensive solutions offer unprecedented levels of functionality, reliability, and scalability. Visit ClearOne at [www.clearone.com](http://www.clearone.com).

Printable releases are available in Investor Relations at <http://investors.clearone.com>

### **Contact:**

ClearOne Marketing  
+1-801-975-7200  
[marketing@clearone.com](mailto:marketing@clearone.com)

Photo - <http://photos.prnewswire.com/prnh/20160601/374645>

Additional assets available online:  [Photos \(1\)](#)

<https://infocomm.vporoom.com/2016-06-02-ClearOne-Introduces-New-Two-Channel-Wireless-Microphone-System>